

CI ANGLE HOSE VALVE JIS 10K

Cast Iron Angle Pattern Hose Valve · JIS 10K Flanged Inlet · Hose Coupling Outlet

BRAND: JINHU ENGINEERING

SKU: SW-0375

SIZE 50A AND 65A

JIS 10K



FIG. 1 | CI ANGLE HOSE VALVE JIS 10K, HOSE COUPLING WITH CAP AND CHAIN

SUPPLIED UNDER THE



PRODUCT OVERVIEW

The SWBM CI Angle Hose Valve is an angle pattern stop valve for hose connected service on deck and in machinery spaces. The inlet is a JIS 10K flange that bolts directly to the header and the outlet carries a bronze hose coupling with a screwed cap and retaining chain, so a wash down or fire hose can be connected and disconnected without tools.

The cast iron body and bonnet carry a bronze or stainless steel disc and seat, giving reliable shut off on sea water and fresh water. The angle pattern removes one elbow from the run, which cuts pressure loss and shortens the installation. Turning through 90 degrees inside the body also makes the valve easier to reach and operate at a bulkhead station.

Valve type	Angle pattern hose valve
Operation	Manual, rising stem handwheel
Body material	Cast iron
Trim	Bronze or stainless steel
Inlet connection	JIS 10K flange
Outlet connection	Hose coupling with cap and chain

TECHNICAL SPECIFICATION

Pattern	Angle, 90 degree flow path	Max. working pressure, non-shock water	1.37 MPa (14 kgf/cm ²) to 120°C
Body and bonnet	Cast iron	Max. working pressure, saturated steam	0.49 MPa (5 kgf/cm ²)
Disc and valve seat	Bronze or stainless steel	Shell test pressure	2.06 MPa (21.0 kgf/cm ²)
Stem	Brass or stainless steel	Seat test pressure	1.51 MPa (15.4 kgf/cm ²)
Packing gland	Bronze	Hose coupling	To be confirmed at order
Packing and gasket	Non asbestos	Manufacturer	Jinhu Engineering Co., Ltd.
Flange standard	JIS B2210, 10K	Country of origin	Korea



PRODUCT DATA SHEET

CI ANGLE HOSE VALVE JIS 10K
Ref. SW-0375 | Rev. 01

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT

#	COMPONENT	MATERIAL
1	Body	Cast iron
2	Bonnet	Cast iron
3	Handwheel	Cast iron
4	Disc	Bronze or stainless steel
5	Valve seat	Bronze or stainless steel
6	Disc nut	Bronze or stainless steel
7	Stem	Brass or stainless steel
8	Packing gland	Bronze
9	Stud bolt and nut	Steel
10	Hose coupling	Bronze
11	Coupling cap	Bronze
12	Retaining chain	Stainless steel

Items 1 to 9 follow the manufacturer parts list for the cast iron angle valve series. Items 10 to 12, the hose coupling, cap and chain, are shown as supplied on the photographed valve and the coupling thread or claw pattern is confirmed at order.

DIMENSIONS

SIZE	DN	FLANGE D (MM)	BOLT C (MM)	BOLT HOLES	L1 (MM)	H (MM)	WEIGHT (KG)
2"	50A	155	120	4-19	120	255	18.2
2.1/2"	65A	175	140	4-19	130	270	25.4

Flange diameters, bolt circles and bolt holes are JIS 10K and are firm. L1 = inlet flange face to valve centreline, H = centreline to top of handwheel, both taken from the manufacturer angle valve table and shown for guidance only: the hose coupling outlet changes the outlet projection and the overall weight. Certified dimensions for the hose valve pattern are issued on request and should be obtained before fabricating pipework.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0375
Size	2" (50A), 2.1/2" (65A)
Inlet	JIS 10K flange
Outlet	Hose coupling, state pattern required
Order example	SW-0375 / 65A / JIS 10K / HOSE COUPLING

A JIS 5K version of the same valve is listed separately. Contact our sales desk for pricing, availability and certification requirements.



PRODUCT DATA SHEET

CI ANGLE HOSE VALVE JIS 10K

Ref. SW-0375 | Rev. 01

PRESSURE AND TEMPERATURE

Non-shock water to 120°C	1.37 MPa (14 kgf/cm²)
Oil and pulsating water	0.98 MPa (10 kgf/cm²)
Air and gas	0.98 MPa (10 kgf/cm²)
Saturated steam	0.49 MPa (5 kgf/cm²)

Working pressures are the JIS 10K figures published by the manufacturer for the cast iron angle valve series in sizes up to 200A. The hose coupling and cap may carry a lower rating than the valve body, so confirm the assembled rating with SWBM before use above 10 bar.

TYPICAL APPLICATIONS

- Deck wash down and hose stations
- Fire main hose connections
- Engine room and pump room service water
- Tank cleaning and bilge hose points
- Shipyard and offshore utility piping
- Shore based industrial hose stations

COMPLIANCE AND QUALITY

- Flanges conform to JIS B2210 nominal pressure 10K
- Angle valve body pattern to the JIS marine valve series
- Hydrostatic shell and seat test before despatch
- Non asbestos packing and gasket materials
- Manufactured under Lloyds Register, DNV GL, Bureau Veritas, Korean Register and ABS approvals
- Class certification and name plate marking supplied against order

INSTALLATION AND OPERATION

- Bolt the inlet flange to the header with a full face gasket to suit JIS 10K
- Mount so the outlet and cap are clear for hose handling
- Keep the cap fitted and the chain attached when the valve is not in use
- Open and close with the handwheel only, never with a bar or wrench
- Repack the gland if weeping appears at the stem
- Cast iron is brittle, protect the valve from impact and freezing

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: Jinhu Engineering

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.