

MS PIPE SCH.80 SMLS 6MTR

Schedule 80 · Seamless · Mild Steel · 6 Metre Length

SCHEDULE 80

SEAMLESS

SIZE 1/2" TO 24"

LENGTH 6 M



FIG. 1 | MS PIPE SCH.80 SMLS 6MTR

PRODUCT OVERVIEW

MS Pipe SCH.80 SMLS 6MTR is seamless mild steel pipe with a schedule 80 wall. Seamless pipe has no weld seam, so there is no line of differing structure along the length, which suits higher pressure and cyclic duty.

The heavier schedule 80 wall raises the pressure capability and leaves more metal for threading and for corrosion allowance. It is the usual choice for hydrocarbon service, steam and any line where threaded connections cut into the wall.

Product type	Seamless pipe
Material	Mild steel, ASTM A53 / A106
Schedule	SCH 80
Size range	1/2" to 24" NPS
Length	6 m
Ends	Plain end, square cut

TECHNICAL SPECIFICATION

Dimensional standard	ASME B36.10M	Surface	Black, mill finish
Material standard	ASTM A53 / A106	OD tolerance	Per the dimensional standard
Manufacturing process	Seamless	Wall tolerance	Minus 12.5% per the dimensional standard
Schedule	SCH 80	Testing	Hydrostatic or eddy current at mill
Standard length	6 m	Certification	EN 10204 3.1 on request
End finish	Plain end, bevel on request	Size range	1/2" to 24" NPS



CONSTRUCTION AND MATERIAL




FIG. 2 | SECTIONAL ARRANGEMENT AND END VIEW

#	ITEM	DETAIL
1	Material	Mild steel, ASTM A53 / A106
2	Manufacture	Seamless
3	Dimensional standard	ASME B36.10M
4	Length	6 m standard mill length
5	Ends	Plain end, square cut, bevelled on request
6	Surface	Black, mill finish, light varnish on request
7	Marking	Size, schedule, heat number, standard
8	Certification	EN 10204 3.1 mill certificate on request

Grade, schedule and end preparation are confirmed against the mill certificate at order stage. Cut lengths and bevelling can be arranged through our machining service.

DIMENSIONS AND WEIGHTS

NPS	DN	OD (MM)	WALL T (MM)	ID (MM)	MASS (KG/M)	PER 6 M (KG)
1/2"	15	21.3	3.73	13.8	1.62	9.7
3/4"	20	26.7	3.91	18.9	2.20	13.2
1"	25	33.4	4.55	24.3	3.24	19.4
1.1/4"	32	42.2	4.85	32.5	4.47	26.8
1.1/2"	40	48.3	5.08	38.1	5.41	32.5
2"	50	60.3	5.54	49.2	7.48	44.9
2.1/2"	65	73.0	7.01	59.0	11.41	68.4
3"	80	88.9	7.62	73.7	15.27	91.6
4"	100	114.3	8.56	97.2	22.32	133.9
5"	125	141.3	9.53	122.2	30.97	185.8
6"	150	168.3	10.97	146.4	42.56	255.4
8"	200	219.1	12.70	193.7	64.64	387.9
10"	250	273.0	15.09	242.8	95.98	575.9
12"	300	323.8	17.48	288.8	132.05	792.3
14"	350	355.6	19.05	317.5	158.11	948.7
16"	400	406.4	21.44	363.5	203.54	1221.3
18"	450	457.2	23.83	409.5	254.68	1528.1
20"	500	508.0	26.19	455.6	311.19	1867.2
24"	600	610.0	30.96	548.1	442.11	2652.7

Outside diameters and wall thicknesses are the nominal values published in ASME B36.10M. Masses are calculated for plain end pipe from the nominal OD and wall using a density of 7 850 kg/m³ and exclude coatings. The product page does not list a size selector, so the range shown is the standard commercially available range. Confirm stocked sizes at enquiry.



ORDERING INFORMATION

FIELD	OPTIONS
Product description	MS PIPE SCH.80 SMLS 6MTR
Size	1/2" to 24" NPS
Schedule	SCH 80
Material	Mild steel, ASTM A53 / A106
Length	6 m standard. Cut lengths on request
Ends	Plain end standard. Bevelled or threaded on request
Order example	MS PIPE SCH.80 SMLS 6MTR / 2" / SCH 80 / 6 M / PLAIN END

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.

COMPLIANCE AND QUALITY

- Dimensions to ASME B36.10M
- Material to ASTM A53 or ASTM A106 as specified
- Hydrostatic or eddy current tested at the mill
- EN 10204 3.1 mill test certificate on request
- Third party inspection can be arranged

HANDLING AND INSTALLATION

- Lift with slings, do not drag pipe over concrete or steel
- Cut square and remove all internal burr before welding
- Bevel to ASME B16.25 for butt welded joints
- Protect galvanising and coatings from weld spatter

TYPICAL APPLICATIONS

- Process and utility pipework
- Structural and support steelwork
- Firewater and cooling water mains
- Compressed air and steam distribution
- Oil and gas surface piping
- General fabrication

STORAGE

- Store clear of the ground on timber or steel supports at even spacing
- Keep stainless steel apart from carbon steel to avoid iron contamination
- Retain end caps and protectors until the pipe is installed
- Support the full length to prevent permanent bow in thin wall sizes

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Pipes and Tubes

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.