

BRASS KING NIPPLE

Hose Tail, Male Threaded · Brass

SKU: SW-0076

BRAND: SW FLOW CONTROLS

SIZE 1/4" TO 2.1/2"

HOSE TAIL



FIG. 1 | BRASS KING NIPPLE, SERRATED TAIL

PRODUCT OVERVIEW

The SWBM Brass King Nipple joins a flexible hose to a threaded pipe connection. The serrated tail enters the hose bore and is secured with a clamp, while the male taper thread screws into any female outlet on a pump, valve or manifold.

Brass gives good corrosion resistance in potable and general water service and is non-sparking, which suits it to fuel transfer and to areas where flammable vapour may be present.

Fitting type	Hose tail nipple
Function	Connects a hose to a male threaded outlet
Material	Brass
End connection	One serrated hose tail, one male thread
Coupling family	Hose Tail
Size range	1/4" to 2.1/2"

TECHNICAL SPECIFICATION

Material	Brass	Working pressure	16 bar (232 psi) nominal
Finish	Natural brass, unplated	Temperature range	-20°C to +100°C nominal
Body form	Hexagon centre	Hose retention	Serrated tail, clamp or ferrule
Threads (BSPT)	ISO 7-1 / BS 21	Electrical	Non-sparking material
Threads (NPT)	ASME B1.20.1	Inspection	Visual and dimensional before despatch
Ends	Hose tail by male thread	Certification	Material certificate on request



BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT

#	FEATURE	DESCRIPTION
1	Serrated hose tail	Multiple barbs for grip under clamping
2	Hexagon	Spanner flats between tail and thread
3	Male thread	Taper R to ISO 7-1, or NPT
4	Full bore	Straight waterway through the nipple
5	Tail lead-in	Chamfered nose to ease hose entry
6	Finish	Natural brass, unplated

One piece fitting. The hose must be secured with a hose clip or bolt clamp suited to the hose and the working pressure.

DIMENSIONS AND WEIGHTS

SIZE	NOMINAL HOSE ID (MM)	MALE THREAD	BODY
1/4"	6	1/4" BSPT	Brass
3/8"	10	3/8" BSPT	Brass
1/2"	13	1/2" BSPT	Brass
3/4"	19	3/4" BSPT	Brass
1"	25	1" BSPT	Brass
1.1/4"	32	1.1/4" BSPT	Brass
1.1/2"	38	1.1/2" BSPT	Brass
2"	51	2" BSPT	Brass
2.1/2"	64	2.1/2" BSPT	Brass

Hose tails are ordered by hose bore and thread size, which are normally the same nominal size. Overall length and across flats are to manufacturer standard and are not stated here. Sizes above 2.1/2" are offered against enquiry.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0076
Size	1/4", 3/8", 1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2"
Thread	BSPT or NPT, as ordered
Material	Brass, natural finish
Order example	SW-0076 / 3/4" / BSPT / BRASS

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRESSURE AND TEMPERATURE

Compressed air	16 bar (232 psi) nominal, non-shock
Water and general service	16 bar (232 psi) nominal at ambient
Temperature range	-20°C to +100°C nominal
Service	Clean, non-corrosive and abrasive media

Pressure and temperature figures are nominal values typical of this class of hose fitting and are not published on the product page. The safe working pressure of a hose assembly is set by the weakest component, usually the hose or the clamp. Confirm the rating with SWBM before the assembly is used on compressed air.

TYPICAL APPLICATIONS

- Compressed air lines on site and in workshops
- Water transfer, dewatering and washdown hoses
- Concrete, plaster and shotcrete delivery lines
- Fuel and lubricating oil transfer
- Irrigation and agricultural pumping
- General plant, quarry and construction hose service

COMPLIANCE AND QUALITY

- Brass construction, good corrosion resistance in water service
- Taper external threads to ISO 7-1 / BS 21
- NPT threads to ASME B1.20.1 available to order
- Serrated hose tails for positive grip under clamping
- Non-sparking, suitable for use around flammable media
- Material test certificate available on request

INSTALLATION AND OPERATION

- Match the coupling to the hose bore, never force an oversize tail
- Push the hose fully home over the serrations before clamping
- Use two clamps per tail on compressed air and abrasive service
- Fit a whip check or safety cable across every air hose joint
- Depressurise the line completely before breaking any coupling
- Inspect seals and serrations before each shift and replace if worn

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.