

MI CAP – FEMALE THREADED

Female Threaded End Cap · Black Malleable Iron

SKU: SW-0139

BRAND: JIANZHI

SIZE 1/8" TO 4"

BSPT / NPT FEMALE



FIG. 1 | MI CAP, FEMALE THREADED, BANDED

PRODUCT OVERVIEW

The SWBM MI Cap seals the threaded end of a pipe or a male fitting without welding. It closes a line that has been commissioned in stages, isolates a section for maintenance, or protects an end left for future extension.

The cap is cast in malleable iron and supplied black, oiled for transport. A banded crown gives the wall thickness needed to hold full line pressure.

Fitting type	End cap, female threaded
Function	Blanks off a male pipe end
Material	Malleable cast iron, black
End connection	Female threaded, one end
Standard	EN 10242 / ISO 49
Size range	1/8" to 4" (DN6 to DN100)

TECHNICAL SPECIFICATION

Dimensional standard	EN 10242 / ISO 49	Threads (BSPT)	ISO 7-1 / EN 10226-1
Material	Malleable cast iron, EN-GJMB-350-10	Threads (NPT)	ASME B1.20.1
Tensile strength	350 N/mm ² minimum	Internal thread	Parallel Rp, ISO 228-1
Elongation	10 per cent minimum	Working pressure	25 bar (363 psi) maximum
Finish	Black, self colour	Figure reference	EN 10242 fig. 300
Protection	Oiled for transport and storage	Ends	Female threaded, one end



PRODUCT DATA SHEET

MI CAP – FEMALE THREADED

Ref. SW-0139 | Rev. 01

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT

#	FEATURE	DESCRIPTION
1	Body	Malleable cast iron, one piece
2	Internal thread	Parallel Rp to ISO 228-1, or NPT
3	Thread run-out	Machined relief at the thread start
4	Closed crown	Solid end wall, no waterway
5	Reinforcing band	Raised band at the mouth of the cap
6	Finish	Black self colour, oiled

One piece fitting with no seals or moving parts. Sealing is made on the threads using PTFE tape or an approved thread sealant. The same figure is stocked hot dip galvanised as a separate item.

DIMENSIONS AND WEIGHTS

SIZE	DN	THREAD	A (MM)	S MAX (MM)
1/8"	6	1/8"	13	15
1/4"	8	1/4"	15	18
3/8"	10	3/8"	17	22
1/2"	15	1/2"	19	26
3/4"	20	3/4"	22	32
1"	25	1"	24	39
1.1/4"	32	1.1/4"	27	48
1.1/2"	40	1.1/2"	27	54
2"	50	2"	32	66
2.1/2"	65	2.1/2"	35	84
3"	80	3"	38	96
4"	100	4"	45	123

a = overall length of the cap, S max = across flats or band diameter. Dimensions are taken from the EN 10242 / ISO 49 pattern for this figure and are nominal. Masses are not published for this item and are therefore not stated. Certified drawings and weights for the make supplied are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0139
Size	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3", 4"
Thread	BSPT or NPT, as ordered
Material	Malleable cast iron, black
Order example	SW-0139 / 2" / BSPT / BLACK

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRODUCT DATA SHEET

MI CAP – FEMALE THREADED
Ref. SW-0139 | Rev. 01

PRESSURE AND TEMPERATURE

Maximum working pressure	25 bar (363 psi), non-shock
Water and general service	25 bar at -20°C to +120°C
Steam and hot media	Derated, confirm the duty with SWBM
Temperature range	-20°C to +200°C

Ratings are those published for malleable cast iron threaded fittings to EN 10242 and apply to non-shock service. Black fittings carry no protective coating, so confirm the medium and the duty with SWBM before use on wet or corrosive service.

TYPICAL APPLICATIONS

- Fire protection and sprinkler pipework
- Compressed air and low pressure gas lines
- Steam and condensate services within rating
- Building services, HVAC and plant rooms
- Pipe framed structures and industrial furniture
- General workshop and utility pipework

COMPLIANCE AND QUALITY

- Manufactured to EN 10242 / ISO 49
- Material EN-GJMB-350-10 malleable cast iron
- Tensile strength 350 N/mm², elongation 10 per cent
- Taper external threads to ISO 7-1 / EN 10226-1
- NPT threads to ASME B1.20.1 available to order
- Air tightness tested before despatch
- Material test certificate EN 10204 3.1 on request

INSTALLATION AND OPERATION

- Clean and de-burr the pipe thread before assembly
- Apply PTFE tape or an approved thread sealant to the male thread only
- Tighten with a pipe wrench on the fitting body or hexagon
- Do not over-tighten, cast iron will crack if it is forced
- Black fittings are not coated, paint or wrap them where corrosion is a risk
- Pressure test the joint before covering or insulating the line

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: Jianzhi

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.