



SS CL150 HEX NIPPLE

Equal Hexagon Nipple · Stainless Steel 316 · Class 150

SKU: SW-0158

BRAND: SW FLOW CONTROLS

SIZE 1/8" TO 4"

BSPT / NPT MALE



FIG. 1 | SS CL150 HEX NIPPLE, MALE BOTH ENDS

PRODUCT OVERVIEW

The SWBM SS CL150 Hex Nipple joins two female threaded outlets on a straight axis. It is the standard way to connect a valve, gauge, strainer or fitting to a female socket, and to make up short spool lengths where a cut pipe would be impractical.

A central hexagon gives a positive spanner grip, so the nipple can be tightened to full sealing torque without damaging the threads. The body is investment cast in austenitic stainless steel.

Fitting type	Equal hexagon nipple
Function	Joins two female threaded outlets
Material	Stainless steel, investment cast
End connection	Male threaded, both ends
Pressure class	Class 150
Size range	1/8" to 4" (DN6 to DN100)

TECHNICAL SPECIFICATION

Material	ASTM A351 CF8M, cast 316	Internal thread	Parallel Rp, ISO 228-1
Pressure class	Class 150	Working pressure	16 bar (232 psi) nominal at ambient
Manufacture	Investment cast, machined threads	Temperature range	-40°C to +200°C nominal
Finish	Pickled and passivated	Dimensional pattern	ISO 4144 / general threaded pattern
Threads (BSPT)	ISO 7-1 / BS 21	Ends	Male threaded, both ends
Threads (NPT)	ASME B1.20.1	Size range	1/8" to 4" (DN6 to DN100)



PRODUCT DATA SHEET

SS CL150 HEX NIPPLE
Ref. SW-0158 | Rev. 01

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT

#	FEATURE	DESCRIPTION
1	Central hexagon	Six flats for spanner tightening
2	Male thread, end 1	Taper R to ISO 7-1, or NPT
3	Male thread, end 2	Taper R to ISO 7-1, or NPT
4	Waterway	Full bore through the nipple
5	Thread run-out	Machined relief at each hexagon face
6	Cast marking	Grade, size and class marked on the body

One piece fitting with no seals or moving parts. Sealing is made on the threads using PTFE tape or an approved thread sealant. The full Class 150 range is stocked in matching sizes.

DIMENSIONS AND WEIGHTS

SIZE	DN	THREAD	A (MM)	S MAX (MM)
1/8"	6	1/8"	29	13
1/4"	8	1/4"	36	17
3/8"	10	3/8"	38	22
1/2"	15	1/2"	44	27
3/4"	20	3/4"	47	32
1"	25	1"	53	41
1.1/4"	32	1.1/4"	57	50
1.1/2"	40	1.1/2"	59	55
2"	50	2"	68	70
2.1/2"	65	2.1/2"	75	85
3"	80	3"	83	100
4"	100	4"	95	130

a = overall length, S max = hexagon across flats. Figures follow the general threaded fitting pattern and are indicative for cast stainless Class 150 fittings, which vary between makes. Confirm with SWBM before they are used for pipe cutting, spool fabrication or any dimensioned submittal. Masses are not published for this item and are therefore not stated.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0158
Size	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3", 4"
Thread	BSPT or NPT, as ordered
Material	Stainless steel, ASTM A351 CF8M
Order example	SW-0158 / 1" / BSPT / SS316

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRESSURE AND TEMPERATURE

Water and general service	16 bar (232 psi) nominal at ambient
Air and gas	16 bar (232 psi) nominal at ambient
Temperature range	-40°C to +200°C nominal
Service	Non-shock, chloride bearing media acceptable

Pressure and temperature figures are nominal values typical of cast stainless Class 150 threaded fittings. Confirm the rating for the make supplied before use in a rated or certified system.

TYPICAL APPLICATIONS

- Potable and process water systems
- Food, beverage and dairy utility lines
- Marine and coastal installations
- Chemical dosing and washdown pipework
- Instrument and sampling connections
- General corrosion resistant pipework

COMPLIANCE AND QUALITY

- Material to ASTM A351 grade CF8M, cast 316
- Taper external threads to ISO 7-1 / BS 21
- NPT threads to ASME B1.20.1 available to order
- Pickled and passivated surface finish
- Air tightness tested before despatch
- Material test certificate EN 10204 3.1 on request
- Suitable for potable water and food contact service

INSTALLATION AND OPERATION

- Clean and de-burr the pipe thread before assembly
- Apply PTFE tape or an approved thread sealant to the male thread only
- Use a dedicated stainless tool set to avoid iron contamination
- Tighten on the fitting body or hexagon, never on the pipe run
- Do not over-tighten, stainless threads gall when they are forced
- Pressure test the joint before covering or insulating the line

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.