



SS316L 3000 PSI UNION, SOCKET WELD

Three Piece Union · Forged Stainless Steel ASTM A182 F316/F316L · Socket Weld Ends to MSS SP-83

BRAND: SW FLOW CONTROLS

SKU: SW-0244

SIZE 1/8" TO 3"

CLASS 3000



FIG. 1 | SS316L 3000 PSI UNION, SOCKET WELD

PRODUCT OVERVIEW

The SWBM SS316L 3000 PSI Socket Weld Union is a three piece fitting that allows a pipe run to be broken and remade without cutting. It is forged from ASTM A182 F316/F316L stainless steel, solution annealed, and made to MSS SP-83 Class 3000.

The male and female ends are fillet welded to the pipe, and the union nut draws them together on an integral metal to metal seat. This gives a leak tight joint that can be opened for maintenance of valves, pumps and instruments.

Fitting type	Union, three piece, forged
End connection	Socket weld, both ends
Material	ASTM A182 F316/F316L forged stainless steel
Pressure class	Class 3000 (3000 lb)
Seat	Integral metal to metal
Size range	1/8" to 3" (DN6 to DN80)

TECHNICAL SPECIFICATION

Design standard	MSS SP-83	Heat treatment	Solution annealed
Material	ASTM A182 F316/F316L forged stainless steel	Marking	MSS SP-25
Pressure class	Class 3000	Surface finish	Natural forged, machined ends
End connection	Socket weld, 2 ends	Temperature range	-196°C to +425°C
Size range	1/8" to 3" (DN6 to DN80)		
Socket dimensions	MSS SP-83 / ASME B16.11		



PRODUCT DATA SHEET

SS316L 3000 PSI UNION, SOCKET WELD

Ref. SW-0244 | Rev. 01

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT (SCHEMATIC)

#	COMPONENT	MATERIAL / DETAIL
1	Female end (thread end)	ASTM A182 F316/F316L forged stainless steel
2	Male end (seat end)	ASTM A182 F316/F316L forged stainless steel
3	Union nut	ASTM A182 F316/F316L forged stainless steel
4	Seat	Integral metal to metal, no gasket
5	Socket (2 nos.)	Bored to MSS SP-83 Class 3000

Three piece assembly. Items 4 and 5 are integral features of the end pieces. Nut thread engagement is a minimum of 4 full threads, class 2A/2B fit.

DIMENSIONS

SIZE	DN	SOCKET BORE B (MM)	SOCKET DEPTH K (MM)	BORE D (MM)	SOCKET WALL C (MM)	LAYING LENGTH E (MM)	LENGTH L (MM)	NUT CLEARANCE N (MM)
1/8"	6	10.9	10.5	6.9	3.18	20.70	41.4	50.8
1/4"	8	14.3	10.5	9.3	3.30	20.70	41.4	50.8
3/8"	10	17.7	10.5	12.6	3.51	23.75	46.0	55.9
1/2"	15	21.9	12.5	15.8	4.09	23.75	49.0	58.4
3/4"	20	27.3	14.0	21.0	4.27	28.60	56.9	66.0
1"	25	34.0	15.0	26.7	4.98	30.25	62.0	78.7
1.1/4"	32	42.8	17.0	35.1	5.28	36.55	71.1	94.0
1.1/2"	40	48.9	17.5	40.9	5.54	38.10	76.5	111.8
2"	50	61.3	22.0	52.5	6.05	41.40	86.1	132.1
2.1/2"	65	74.0	25.0	62.7	7.67	56.90	102.4	149.9
3"	80	90.0	25.0	78.0	8.31	58.70	109.0	175.3

B = socket bore, K = socket depth, D = waterway bore, C = socket wall, E = laying length between socket bottoms, L = assembled length (nominal), N = clearance diameter of assembled nut. Dimensions from the manufacturer standard, in accordance with MSS SP-83. Dimensions are nominal. Weights and certified drawings are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0244
Size	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3"
Class	Class 3000
End connection	Socket weld to MSS SP-83
Certification	EN 10204 3.1 on request
Order example	SW-0244 / 1" / CL3000 / SW / F316L

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRODUCT DATA SHEET

SS316L 3000 PSI UNION, SOCKET WELD

Ref. SW-0244 | Rev. 01

PRESSURE AND TEMPERATURE

Pressure class	Class 3000 to MSS SP-83
Rating basis	For use with Sch 80 pipe, same NPS
Material group	ASTM A182 F316/F316L, ASME B16.5 Gr. 2.2
Temperature range	-196°C to +425°C

Class 3000 is a class designation, not a working pressure. The allowable pressure equals that of the matching pipe schedule, size and design temperature under ASME B31.3 or the governing code. Confirm duty with SWBM before use on media or temperatures outside normal service.

TYPICAL APPLICATIONS

- Break points at pumps, valves and equipment
- Instrument and analyser connections
- Oil and gas production and process piping
- Steam, condensate and utility lines
- Skid packages needing removable spools
- Marine, offshore and shipyard piping

COMPLIANCE AND QUALITY

- Dimensions and testing to MSS SP-83, Class 3000
- Material to ASTM A182 F316/F316L, solution annealed
- Integral metal to metal seat, no gasket
- Marking to MSS SP-25: maker, material, class and size
- Material test certificate EN 10204 3.1 on request
- Third party inspection on request

INSTALLATION AND OPERATION

- Remove the nut and separate the ends before welding
- Insert the pipe fully, then withdraw about 1.6 mm before fillet welding each end
- Weld to ASME B31.3 with a qualified procedure and let the ends cool fully
- Protect the seat faces from spatter and damage during welding
- Align the ends before tightening, never use the nut to pull pipe into line
- Tighten the nut with a spanner on the flats while holding the female end

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.