SS316L 10000 PSI HEX NIPPLE NPT

Hex Nipple · Stainless Steel 316L · NPT Threaded · 10,000 PSI

BRAND: SW FLOW CONTROLS | SKU: SW-0266 | SIZE 1/4" TO 1" | 10,000 PSI / 690 BAR



FIG. 1 | SS316L 10000 PSI HEX NIPPLE NPT

PRODUCT OVERVIEW

The SWBM SS316L 10000 PSI Hex Nipple joins two female NPT fittings, valves or instruments of the same size. Both ends carry male NPT taper threads.

The integral hex centre takes a standard spanner, giving a short and rigid connection rated 10,000 PSI in corrosion resistant 316L stainless steel.

Fitting type	**Hex nipple**
End connection	**Male NPT, both ends**
Material	**Stainless steel 316L**
Pressure rating	**10,000 PSI (690 bar)**
Thread	**NPT, ASME B1.20.1**
Size range	**1/4" to 1" (DN8 to DN25)**

TECHNICAL SPECIFICATION

Design standard	**Manufacturer standard**
Material	**Stainless steel 316L**
Pressure rating	**10,000 PSI (690 bar)**
End connection	**Male NPT, both ends**
Size range	**1/4" to 1" (DN8 to DN25)**
Threads (NPT)	**ASME B1.20.1**

Body	**One piece, solid section**
Service	**Liquids and gases**
Surface finish	**Machined, bright**
Marking	**Material, size, thread, rating, heat no.**

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT (SCHEMATIC)

#	COMPONENT	MATERIAL / DETAIL
1	Body	Stainless steel 316L, solid
2	Male end	Male NPT to ASME B1.20.1
3	Opposite male end	Male NPT to ASME B1.20.1
4	Internal passage	Through bore
5	Hex	Spanner flats

One piece construction. Items 2 to 5 are integral features, listed to identify the critical dimensional and inspection points.

DIMENSIONS

SIZE	DN	THREAD	THREADS PER INCH	PIPE OD (MM)	HAND TIGHT L1 (MM)	EFFECTIVE THREAD L2 (MM)
1/4"	8	1/4" NPT	18	13.7	5.1	10.2
3/8"	10	3/8" NPT	18	17.1	6.1	10.4
1/2"	15	1/2" NPT	14	21.3	8.1	13.6
3/4"	20	3/4" NPT	14	26.7	8.6	13.9
1"	25	1" NPT	11.5	33.4	10.2	17.3

Thread data per ASME B1.20.1 (NPT) and pipe OD per ASME B36.10 for the mating pipe. Body dimensions follow the manufacturer standard and are not published here. Certified drawings, body dimensions and weights are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0266
Size	1/4", 3/8", 1/2", 3/4", 1"
Thread	NPT to ASME B1.20.1
Pressure rating	10,000 PSI (690 bar)
Certification	EN 10204 3.1 on request
Order example	**SW-0266 / 1/2" / NPT / SS316L**

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.

PRESSURE AND TEMPERATURE

Rated pressure	**10,000 PSI (690 bar), as listed**
Service basis	**Ambient temperature, non-shock**
Material	**Stainless steel 316L**
Threads	**NPT to ASME B1.20.1**

The 10,000 PSI rating is taken from the product listing and applies at ambient temperature in non-shock service. The system rating is set by its lowest rated component. Derating for elevated temperature or cyclic duty must be confirmed with SWBM.

TYPICAL APPLICATIONS

- Hydraulic power units and test benches
- Chemical injection and wellhead control lines
- High pressure instrument and gauge connections
- Oil and gas, petrochemical and power plants
- Marine and offshore hydraulic systems
- Pressure test rigs and manifolds

COMPLIANCE AND QUALITY

- Stainless steel 316L body
- NPT threads to ASME B1.20.1
- Rated 10,000 PSI (690 bar), non-shock service
- Marked with material, size, thread, rating and heat number
- Material test certificate EN 10204 3.1 on request
- Pressure test and third party inspection on request

INSTALLATION AND OPERATION

- Clean and inspect the threads before assembly
- Apply PTFE tape or a high pressure thread sealant to the male thread only
- Use an anti-galling compound where permitted, stainless threads can gall if dry
- Tighten with a correctly sized spanner while holding the mating part
- Confirm every component in the assembly is rated for the working pressure
- Pressure test the completed assembly before putting it into service

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.