BRASS CAMLOCK PART-DP

Type DP Cam and Groove Dust Plug · Brass · A-A-59326 pattern

BRAND: SW FLOW CONTROLS | SKU: SW-0018 | SIZE 1/2" to 6" | UP TO 16 BAR / 232 PSI



FIG. 1 | BRASS CAMLOCK PART-DP, TYPE DP DUST PLUG

PRODUCT OVERVIEW

The SWBM Brass Camlock Part-DP is a Type DP cam and groove fitting that closes an open female camlock coupler to keep out dirt and moisture and to prevent spillage. It suits quick, repeated connection and disconnection of hoses and pipework in transfer duties.

The male groove end locks into any matching camlock coupler of the same size, whose cam arms and gasket make the seal. The connection is made or broken by hand, without tools. The brass body resists corrosion from water, hydraulic oil, coolants, gasoline and petroleum products.

Product type	**Type DP, dust plug**
End 1	**Male camlock adapter (groove)**
End 2	**Closed end**
Body material	**Brass**
Pressure rating	**Up to 16 bar (232 psi)**
Size range	**1/2" to 6" (DN15 to DN150)**

TECHNICAL SPECIFICATION

Design pattern	**A-A-59326 pattern**
Body	**Brass**
Connection	**None**
Seal	**Gasket of mating coupler**
Cam arms	**Not applicable**
Pins and pull rings	**Not applicable**

Working pressure	**Up to 16 bar, all sizes**
Temperature	**-20°C to +100°C, NBR seal**
Mates with	**Type B, C and D couplers**
Operation	**Push fit into coupler**
Excluded service	**Compressed air, steam**
Size range	**1/2" to 6"**

BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT, SCHEMATIC

#	COMPONENT	MATERIAL
1	Body, one piece	Brass

One piece construction with no loose parts. The joint is sealed by the gasket of the mating coupler. A chain or cord can be attached at the lug where fitted.

DIMENSIONS AND WEIGHTS

SIZE	DN	CONNECTION	A	B	C
3/4"	20	Closed	38	30.2	32.04
1"	25	Closed	48.5	36.5	36.7
1.1/4"	32	Closed	54	39.7	45.45
1.1/2"	40	Closed	58.6	41.67	53.4
2"	50	Closed	66	48	63.03
2.1/2"	65	Closed	68.2	53	75.78
3"	80	Closed	71	56	91.47
4"	100	Closed	72.79	52.78	119.52
6"	150	Closed	95.53	58.6	175.93

All dimensions in mm. A = overall length, B = adapter length, C = adapter outside diameter. Sizes 1/2" and 5" against enquiry. Dimensions follow the aluminium A-A-59326 pattern and are nominal for brass; brass weights on request. Dimensions and weights are nominal and given for guidance only. Certified drawings are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0018
Size	1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3", 4", 5", 6"
Material	Brass
Order example	**SW-0018 / 2"**

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.

PRESSURE AND TEMPERATURE

Maximum working pressure	**Up to 16 bar (232 psi)**
Applies to	**All sizes and configurations**
Gasket	**NBR (Buna-N)**
Temperature	**-20°C to +100°C, NBR seal**

Maximum working pressure at +21°C with a standard NBR gasket. The rating of a joint is set by the lower rated of the two mating parts. Not for compressed air or steam service. Confirm duty with SWBM for elevated temperature or aggressive media.

COMPLIANCE AND QUALITY

- Interchangeable with A-A-59326 (MIL-C-27487) pattern fittings
- Body: Brass
- Interchangeable with standard cam and groove fittings of the same size
- Pressure ratings per size shown on this sheet

TYPICAL APPLICATIONS

- Marine fuelling and bunkering hoses
- Petroleum and oil product transfer
- Water, hydraulic oil and coolant lines
- Chemical transfer, subject to compatibility
- Oil and gas service
- General industrial fluid transfer

INSTALLATION AND OPERATION

- Keep the groove and sealing face clean and free of damage
- Insert fully into the coupler before closing its cam arms
- Release pressure and drain the line before disconnecting

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.