

BRASS CAMLOCK PART-E

Type E Cam and Groove Male Adapter x Hose Shank · Brass · Hose Shank

BRAND: SW FLOW CONTROLS

SKU: SW-0019

SIZE 1/2" to 6"

UP TO 16 BAR / 232 PSI



FIG. 1 | BRASS CAMLOCK PART-E, TYPE E MALE ADAPTER X HOSE SHANK

PRODUCT OVERVIEW

The SWBM Brass Camlock Part-E is a Type E cam and groove fitting that terminates a hose with a male camlock adapter for quick connection to couplers. It suits quick, repeated connection and disconnection of hoses and pipework in transfer duties.

The male groove end locks into any matching camlock coupler of the same size, whose cam arms and gasket make the seal. The connection is made or broken by hand, without tools. The brass body resists corrosion from water, hydraulic oil, coolants, gasoline and petroleum products.

Product type	Type E, male adapter x hose shank
End 1	Male camlock adapter (groove)
End 2	Hose shank
Body material	Brass
Pressure rating	Up to 16 bar (232 psi)
Size range	1/2" to 6" (DN15 to DN150)

TECHNICAL SPECIFICATION


Design pattern	A-A-59326 pattern	Working pressure	Up to 16 bar, all sizes
Body	Brass	Temperature	-20°C to +100°C, NBR seal
Connection	Hose shank	Mates with	Type B, C, D and DC
Seal	Gasket of mating coupler	Operation	Push fit into coupler
Cam arms	Not applicable	Excluded service	Compressed air, steam
Pins and pull rings	Not applicable	Size range	1/2" to 6"



PRODUCT DATA SHEET

BRASS CAMLOCK PART-E
Ref. SW-0019 | Rev. 01

BILL OF MATERIALS



#	COMPONENT	MATERIAL
1	Body, one piece	Brass

One piece construction with no loose parts. The joint is sealed by the gasket of the mating coupler.

FIG. 2 | SECTIONAL ARRANGEMENT, SCHEMATIC

DIMENSIONS AND WEIGHTS

SIZE	DN	CONNECTION	A	B	C
3/4"	20	Hose shank	89	50.8	21
1"	25	Hose shank	106	57.2	27
1.1/4"	32	Hose shank	109.6	57.2	33.75
1.1/2"	40	Hose shank	114.6	61	39.88
2"	50	Hose shank	145.23	85.7	52.6
2.1/2"	65	Hose shank	145.1	81.5	66.2
3"	80	Hose shank	163.6	101.6	77.79
4"	100	Hose shank	175	108	103.99
6"	150	Hose shank	238	181.5	154.8

All dimensions in mm. A = overall length, B = hose shank length, C = hose shank outside diameter. Sizes 1/2" and 5" against enquiry. Dimensions follow the aluminium A-A-59326 pattern and are nominal for brass; brass weights on request. Dimensions and weights are nominal and given for guidance only. Certified drawings are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0019
Size	1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3", 4", 5", 6"
Material	Brass
Order example	SW-0019 / 2"

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRESSURE AND TEMPERATURE

Maximum working pressure	Up to 16 bar (232 psi)
Applies to	All sizes and configurations
Gasket	NBR (Buna-N)
Temperature	-20°C to +100°C, NBR seal

Maximum working pressure at +21°C with a standard NBR gasket. The rating of a joint is set by the lower rated of the two mating parts. Not for compressed air or steam service. Confirm duty with SWBM for elevated temperature or aggressive media.

TYPICAL APPLICATIONS

- Marine fuelling and bunkering hoses
- Petroleum and oil product transfer
- Water, hydraulic oil and coolant lines
- Chemical transfer, subject to compatibility
- Oil and gas service
- General industrial fluid transfer

COMPLIANCE AND QUALITY

- Interchangeable with A-A-59326 (MIL-C-27487) pattern fittings
- Body: Brass
- Interchangeable with standard cam and groove fittings of the same size
- Pressure ratings per size shown on this sheet

INSTALLATION AND OPERATION

- Push the hose fully over the shank
- Secure with hose clamps or ferrules suited to the hose and pressure
- Keep the groove and sealing face clean and free of damage
- Insert fully into the coupler before closing its cam arms
- Release pressure and drain the line before disconnecting

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.