

PVC CAMLOCK PART-C

Type C Cam and Groove Female Coupler x Hose Shank · PVC / polypropylene · Hose Shank

BRAND: SW FLOW CONTROLS

SKU: SW-0031

SIZE 1" to 2"

UP TO 6.9 BAR / 100 PSI



FIG. 1 | PVC CAMLOCK PART-C, TYPE C FEMALE COUPLER X HOSE SHANK

PRODUCT OVERVIEW

The SWBM PVC Camlock Part-C is a Type C cam and groove fitting that terminates a hose with a camlock coupler for quick connection to adapters. It suits quick, repeated connection and disconnection of hoses and pipework in transfer duties.

Two cam arms on the coupler lock over the groove of the mating adapter and compress the gasket to seal the joint. The connection is made or broken by hand, without tools. The thermoplastic body is light, non-corrosive and resistant to many chemicals, acids and corrosive fluids.

Product type	Type C, female coupler x hose shank
End 1	Female camlock coupler (cam arms)
End 2	Hose shank
Body material	PVC / polypropylene
Pressure rating	Up to 6.9 bar (100 psi)
Size range	1" to 2" (DN25 to DN50)

TECHNICAL SPECIFICATION

Design pattern	A-A-59326 pattern	Working pressure	6.9 bar, all sizes
Body	Thermoplastic, PVC / polypropylene	Temperature	Ambient, consult SWBM for heat
Connection	Hose shank	Mates with	Type A, E, F and DP
Seal	Gasket, EPDM or NBR, to order	Operation	Hand operated cam lever
Cam arms	Stainless steel	Excluded service	Compressed air, steam
Pins and pull rings	Steel	Size range	1" to 2"



BILL OF MATERIALS




FIG. 2 | SECTIONAL ARRANGEMENT, SCHEMATIC

#	COMPONENT	MATERIAL
1	Body	Thermoplastic, PVC / polypropylene
2	Cam arm (2 per coupler)	Stainless steel
3	Cam arm pin	Steel
4	Pull ring	Steel, zinc plated
5	Gasket	EPDM or NBR, to order

Gasket and cam arms are replaceable. Safety clips may be fitted to the pull rings to stop the arms opening. Alternative gasket elastomers against enquiry.

DIMENSIONS AND WEIGHTS

SIZE	DN	END 1	END 2	WORKING PRESSURE	LENGTH AND WEIGHT
1"	25	Coupler	Hose shank	6.9 bar (100 psi)	On request
1.1/2"	40	Coupler	Hose shank	6.9 bar (100 psi)	On request
2"	50	Coupler	Hose shank	6.9 bar (100 psi)	On request

Size refers to the camlock end size. Camlock ends follow the A-A-59326 pattern and mate with standard fittings of the same size. Overall length and weight are given on the certified drawing, issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0031
Size	1", 1.1/2", 2"
Gasket	EPDM or NBR, state with order
Material	PVC / polypropylene
Order example	SW-0031 / 2" / EPDM

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.



PRESSURE AND TEMPERATURE

Size 1" to 2"

6.9 bar (100 psi)

Low pressure rating for thermoplastic camlocks at ambient temperature. Pressure capacity falls as temperature rises. The rating of a joint is set by the lower rated of the two mating parts. Not for compressed air or steam service. Confirm chemical compatibility and duty with SWBM.

TYPICAL APPLICATIONS

- Agricultural spraying and irrigation
- Chemical processing, subject to compatibility
- Low pressure fluid transfer
- Suction and delivery of water and chemicals
- Dry bulk and powder handling
- Tank, IBC and drum connections

COMPLIANCE AND QUALITY

- Camlock ends to the A-A-59326 (MIL-C-27487) pattern
- Body: Thermoplastic, PVC / polypropylene
- Interchangeable with standard cam and groove fittings of the same size
- Stainless steel cam arms, steel pins and steel, zinc plated pull rings
- Replaceable gasket, EPDM or NBR
- Non-corrosive thermoplastic body

INSTALLATION AND OPERATION

- Push the hose fully over the shank
- Secure with hose clamps or ferrules suited to the hose and pressure
- Open both cam arms fully before inserting the adapter
- Close both arms together and secure the pull rings or safety clips
- Check the gasket before each connection and replace if cut or swollen
- Release pressure and drain the line before disconnecting

COMPANY

Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES

info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE

www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.