PVC CAMLOCK PART-DC

Type DC Cam and Groove Dust Cap · PVC / polypropylene · A-A-59326 pattern

BRAND: SW FLOW CONTROLS | SKU: SW-0033 | SIZE 1" to 2" | UP TO 6.9 BAR / 100 PSI

FIG. 1 | PVC CAMLOCK PART-DC, TYPE DC DUST CAP

PRODUCT OVERVIEW

The SWBM PVC Camlock Part-DC is a Type DC cam and groove fitting that closes an open male camlock adapter to keep out dirt and moisture and to prevent spillage. It suits quick, repeated connection and disconnection of hoses and pipework in transfer duties.

Two cam arms on the coupler lock over the groove of the mating adapter and compress the gasket to seal the joint. The connection is made or broken by hand, without tools. The thermoplastic body is light, non-corrosive and resistant to many chemicals, acids and corrosive fluids.

Product type	**Type DC, dust cap**
End 1	**Female camlock coupler (cam arms)**
End 2	**Closed end**
Body material	**PVC / polypropylene**
Pressure rating	**Up to 6.9 bar (100 psi)**
Size range	**1" to 2" (DN25 to DN50)**

TECHNICAL SPECIFICATION

Design pattern	**A-A-59326 pattern**
Body	**Thermoplastic, PVC / polypropylene**
Connection	**None**
Seal	**Gasket, EPDM or NBR, to order**
Cam arms	**Stainless steel**
Pins and pull rings	**Steel**

Working pressure	**6.9 bar, all sizes**
Temperature	**Ambient, consult SWBM for heat**
Mates with	**Type A, E and F adapters**
Operation	**Hand operated cam lever**
Excluded service	**Compressed air, steam**
Size range	**1" to 2"**

BILL OF MATERIALS



FIG. 2 | SECTIONAL ARRANGEMENT, SCHEMATIC

#	COMPONENT	MATERIAL
1	Body	Thermoplastic, PVC / polypropylene
2	Cam arm (2 per coupler)	Stainless steel
3	Cam arm pin	Steel
4	Pull ring	Steel, zinc plated
5	Gasket	EPDM or NBR, to order

Gasket and cam arms are replaceable. Safety clips may be fitted to the pull rings to stop the arms opening. Alternative gasket elastomers against enquiry.

DIMENSIONS AND WEIGHTS

SIZE	DN	END 1	END 2	WORKING PRESSURE	LENGTH AND WEIGHT
1"	25	Coupler	Closed	6.9 bar (100 psi)	On request
1.1/2"	40	Coupler	Closed	6.9 bar (100 psi)	On request
2"	50	Coupler	Closed	6.9 bar (100 psi)	On request

Size refers to the camlock end size. Camlock ends follow the A-A-59326 pattern and mate with standard fittings of the same size. Overall length and weight are given on the certified drawing, issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0033
Size	1", 1.1/2", 2"
Gasket	EPDM or NBR, state with order
Material	PVC / polypropylene
Order example	**SW-0033 / 2" / EPDM**

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.

PRESSURE AND TEMPERATURE

Size 1" to 2"	**6.9 bar (100 psi)**

Low pressure rating for thermoplastic camlocks at ambient temperature. Pressure capacity falls as temperature rises. The rating of a joint is set by the lower rated of the two mating parts. Not for compressed air or steam service. Confirm chemical compatibility and duty with SWBM.

COMPLIANCE AND QUALITY

- Camlock ends to the A-A-59326 (MIL-C-27487) pattern
- Body: Thermoplastic, PVC / polypropylene
- Interchangeable with standard cam and groove fittings of the same size
- Stainless steel cam arms, steel pins and steel, zinc plated pull rings
- Replaceable gasket, EPDM or NBR
- Non-corrosive thermoplastic body

TYPICAL APPLICATIONS

- Agricultural spraying and irrigation
- Chemical processing, subject to compatibility
- Low pressure fluid transfer
- Suction and delivery of water and chemicals
- Dry bulk and powder handling
- Tank, IBC and drum connections

INSTALLATION AND OPERATION

- Open both cam arms fully before inserting the adapter
- Close both arms together and secure the pull rings or safety clips
- Check the gasket before each connection and replace if cut or swollen
- Release pressure and drain the line before disconnecting

COMPANY
Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES
info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE
www.swbm-fittings.com
Brand: SW Flow Controls

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.