SS316 FLEXIBLE CONNECTOR UNION TYPE

Twin Sphere Rubber Expansion Joint · Female Threaded Union Ends · Stainless Steel 316

BRAND: JARTA | SKU: SW-0039 | SIZE 1/2" TO 3" | 10 BAR / 150 PSI



FIG. 1 | SS316 UNION TYPE, TWIN SPHERE

PRODUCT OVERVIEW

The SWBM SS316 Flexible Connector Union Type is a twin sphere rubber expansion joint fitted with stainless steel 316 female threaded union ends. It absorbs vibration, noise and pipe movement on small bore pumped lines while resisting chloride attack at the metal connections, making it suited to marine, coastal and process duties.

The moulded EPDM body is reinforced with nylon cord fabric plies and steel bead wire rings. The twin sphere form gives greater movement capacity and lower reaction forces than a single sphere of the same length. The union ends allow the joint to be fitted and removed without disturbing the pipework.

Product type	**Twin sphere rubber expansion joint**
Body material	**EPDM rubber, nylon cord reinforced**
End connection	**Female threaded union, BSPT / NPT**
End material	**Stainless steel 316**
Pressure rating	**10 bar (150 psi) at ambient**
Size range	**1/2" to 3" (DN15 to DN80)**

TECHNICAL SPECIFICATION

Design type	**Twin sphere, moulded and vulcanised**	Working pressure	**10 bar (150 psi), non-shock**
Body construction	**EPDM inner liner and outer cover**	Test pressure	**15 bar (1.5 x rated)**
Reinforcement	**Nylon cord plies, steel bead wire**	Vacuum service	**660 mmHg (26 in. Hg)**
Union material	**Stainless steel 316**	Temperature range	**-20°C to +110°C**
Threads (BSPT)	**ISO 7-1 / BS 21**	Axial movement	**22 mm compression, 6 mm extension**
Threads (NPT)	**ASME B1.20.1**	Overall length	**Per dimensions table**

MEDIA AND COMPOUND SELECTION

COMPOUND	TYPICAL MEDIA	TEMPERATURE RANGE
EPDM	Water, chilled and condenser water, dilute acids and alkalis	**-20°C to +110°C**
NBR	Mineral oil, diesel, lubricating oil and oily water	**-20°C to +90°C**
CR (neoprene)	General water, sea water, weak acids, outdoor exposure	**-20°C to +100°C**
NR	Abrasive slurries and sand laden water	**-20°C to +80°C**

EPDM is supplied as standard and must not be used on mineral oil or hydrocarbon media. State the service medium, temperature and pressure at enquiry.

BILL OF MATERIALS



FIG. 2 | SECTIONAL ARRANGEMENT

#	COMPONENT	MATERIAL
1	Outer cover	EPDM rubber, weather and ozone resistant
2	Reinforcement ply	Nylon cord fabric, multiple plies
3	Bead wire ring	Steel wire rope, vulcanised in
4	Union nut	Stainless steel 316
5	Union tailpiece, female threaded	Stainless steel 316
6	Union seat seal	EPDM gasket
7	Inner liner	EPDM rubber, smooth bore

NBR body compound can be supplied for oil bearing media. Threads are supplied BSPT unless NPT is stated on the order.

DIMENSIONS AND MOVEMENTS

SIZE	DN	THREAD	L OVERALL (MM)	AXIAL COMP. (MM)	AXIAL EXT. (MM)	LATERAL (MM)	ANGULAR	WEIGHT (KG)
1/2"	15	1/2"	203	22	6	22	±32°	0.49
3/4"	20	3/4"	203	22	6	22	±32°	0.70
1"	25	1"	203	22	6	22	±25°	1.20
1.1/4"	32	1.1/4"	203	22	6	22	±21°	1.58
1.1/2"	40	1.1/2"	203	22	6	22	±18°	1.96
2"	50	2"	203	22	6	22	±13°	2.59
2.1/2"	65	2.1/2"	244	22	6	22	±11°	4.25
3"	80	3"	244	22	6	22	±9°	5.27

L = overall length between the mating pipe thread faces. Movements are non concurrent maxima and weights are for the complete assembly. Figures are nominal, certified drawings are issued on request.

ORDERING INFORMATION

FIELD	OPTIONS
Product code	SW-0039
Size	1/2", 3/4", 1", 1.1/4", 1.1/2", 2", 2.1/2", 3"
Thread	BSPT or NPT, female
Body compound	EPDM standard. NBR on request
End material	Stainless steel 316. SS304 on request
Order example	**SW-0039 / 1.1/2" / BSPT / EPDM**

Stock held in Dubai for fast despatch across the UAE and GCC. Contact our sales desk for pricing, availability, project quantities and certification requirements.

PRESSURE AND TEMPERATURE

Working pressure (EPDM)	**10 bar (150 psi) at ambient**
Test pressure	**15 bar, 1.5 x rated**
Vacuum service	**660 mmHg (26 in. Hg)**
Temperature range	**-20°C to +110°C**
Peak temperature	**+120°C, intermittent**
Angular movement	**Per dimensions table**

Ratings apply to cold, non-shock water service with an EPDM body. Derating applies above +80°C and should be confirmed with SWBM before order. EPDM is not suitable for mineral oil or hydrocarbon service, specify an NBR body for those media.

TYPICAL APPLICATIONS

- Sea water and marine service lines
- Small pump and circulator connections
- Chilled water and HVAC branch lines
- Food, dairy and process utility piping
- Chemical dosing and effluent transfer
- Coastal and high humidity plant rooms

COMPLIANCE AND QUALITY

- Twin sphere body moulded and vulcanised, nylon cord reinforced
- Union ends in stainless steel 316 for chloride service
- Female threads to ISO 7-1 / BS 21 (BSPT) or ASME B1.20.1 (NPT)
- Hydrostatic shell test at 1.5 x rated pressure
- 100% pressure tested before despatch
- EPDM compound suitable for potable and chilled water
- Material and test certificate EN 10204 3.1 on request

INSTALLATION AND OPERATION

- Flush the line thoroughly before installation to clear weld slag, sand and debris
- Align the pipe ends and set the gap to the overall length of the joint before making up the unions
- Do not stretch or compress the rubber body to take up a gap in the pipework
- Tighten on the union nut flats only, never on the rubber body or the reinforcement
- Apply PTFE tape or an approved sealant to the mating male thread only
- Support the pipework on both sides so that the joint carries no pipe weight
- Keep the joint clear of heat sources, direct sunlight, ozone and sharp tools

COMPANY
Sunel Wala Building Materials
Trading Co. LLC (SWBM)
Dubai, United Arab Emirates

SALES ENQUIRIES
info@swbm-fittings.com
Tel: +971 4 238 5652
Mobile / WhatsApp: +971 50 748 1772

ONLINE
www.swbm-fittings.com
Brand: JARTA

The information in this data sheet is provided in good faith and is believed to be accurate at the date of issue. Dimensions, weights and ratings are nominal and may vary with the manufacturer and production batch. It remains the responsibility of the purchaser to confirm that the product is suitable for the intended service conditions. Sunel Wala Building Materials Trading Co. LLC reserves the right to amend specifications without prior notice. This document does not form part of any contract of sale.